

*List of sports supported:*

*Basketball (FIBA levels 2 and 3) - Handball (national) - Volleyball (international)  
 Tennis - Table tennis - Badminton - Rink hockey - Floorball - Futsal*



*Also available  
 as HOME/GUEST version:*



#### General characteristics

- Indoor use
- SMD LED technology.
- Brightness adjustable via the Scorepad touch screen. Can be adjusted during a match.
- Team names can be programmed from the Scorepad touchscreen keyboard.
- Built-in horn (120dB at 1 metre).

#### Certification and compliance for the marking CE

- RED (radio): EN 301 489-3, EN 300 220-2.
- Electromagnetic compatibility (EMC): EN 55024, EN 55032.
- Low voltage: EN 60950.

#### Model reference nos.

- 916 221..... 8T215 HOME/GUEST.
- 916 222..... 8T215 Alpha.
- 916 271..... 8T215 HOME/GUEST + Scorepad.
- 916 272..... 8T215 Alpha + Scorepad.

## Scoreboard display

	Display description	Display characteristics
<b>A</b>	Game clock or local time or time-out timer.....	4 yellow 15cm digits per team.
<b>B</b>	Clock stopped indicator.....	1 red dot.
<b>C</b>	Team fouls.....	1 red 10cm digit per team.
<b>Alpha-numerical version:</b>		
	Team names.....	Max. 7 characters, yellow, 10cm, per team.
<b>D</b>	Scrolling messages.....	Max. 60 characters, yellow, 10cm.
<b>HOME/GUEST version:</b>		
	Stickers.....	Yellow 12cm letters.
<b>E</b>	Time-out indicators.....	3 yellow dots per team.
<b>F</b>	Period number.....	1 yellow 10cm digit.
<b>G</b>	Score.....	3 red 15cm digits per team.
<b>H</b>	Penalty time count or reminder of last individual foul or time-out count or result of previous set.....	4 yellow 10cm digits per team.

## Technical data

Dimensions.....	L1200 x H1000 x D65.5/64mm.
Weight.....	80kg.
Scoreboard construction.....	Steel.
Protection ratings.....	IP20, IK09 (DIN standard 18032).
Optimal reading distance.....	60m.
Reading angle.....	160°.
Power supply.....	230V AC, 50/60Hz.
Power consumption.....	280W.
Protection level.....	16A circuit breaker - curve D.
Communication.....	Keyboard/8T215 link by wire or HF radio.

