

List of sports supported:

**Basketball (FIBA levels 2 and 3) - Handball (national) - Volleyball (international)
Tennis - Table tennis - Badminton - Rink hockey - Floorball - Futsal**



**Also available
as HOME/GUEST version:**



General characteristics

- Indoor use
- SMD LED technology.
- Brightness adjustable via the Scorepad touch screen. Can be adjusted during a match.
- Team names can be programmed from the Scorepad touchscreen console.
- Built-in horn (120dB at 1 metre).

Certification and compliance

- R&TTE (radio). 869MHz radio communication.
- CE mark.
- Electromagnetic compatibility (EMC).
- Low voltage.

Model reference nos.

- 916 205..... 8025 HOME/GUEST.
- 916 206..... 8025 Alpha.
- 916 255..... 8025 HOME/GUEST + Scorepad.
- 916 256..... 8025 Alpha + Scorepad.

Scoreboard display

Display description	Display characteristics
A Game clock or local time or time-out timer.....	4 yellow 25cm digits per team.
B Clock stopped indicator.....	1 red dot.
C Team fouls.....	1 red 20cm digit per team.
Alpha-numerical version:	
Team names.....	Max. 11 characters, yellow, 12cm, per team.
D Scrolling messages.....	Max. 100 characters, yellow, 12cm.
LOC/VISIT version:	
Stickers.....	Yellow 12cm letters.
E Time-out indicators.....	3 yellow dots per team.
F Period number.....	1 yellow 20cm digit.
G Score.....	3 red 25cm digits per team.

Technical data

Dimensions.....	L2000 x H1000 x D65.5mm.
Weight.....	50kg.
Scoreboard construction.....	Steel.
Protection ratings.....	IP20, IK09 (DIN standard 18032).
Optimal reading distance.....	120m.
Reading angle.....	160°.
Power supply.....	230V AC, 50/60Hz.
Power consumption.....	280W.
Protection level.....	16 A circuit breaker - curve D.
Communication.....	Console/8025 link by wire or HF radio.

